



## ProLite B1780SD-1

### Perfect choice for office

The 17" ProLite B1780SD designed for business usage is a LED-backlit monitor with Height Adjustability and Screen Rotation allowing you to set the perfect position of the screen ensuring ergonomic posture and optimal viewing comfort. The 5ms response time and high contrast make the B1780SD ideal for a wide range of business applications. sRGB and gamma correction functions permit even the finest nuances of colour to be set accurately. The ProLite B1780SD includes DVI and VGA connectivity and is available in white.

### DISPLAY CHARACTERISTICS

Diagonal	17"
Panel	TN LED
Display area h x w	270.3 x 337.9 mm; 10.6" x 13.3"
Response time	5 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	250 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 ( 1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	5 : 4

### POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	14 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

### DIMENSIONS & WEIGHT

Dimensions w x h x d	370 x 399.5 (529.5) x 230 mm
Weight	4.4 kg

### INTERFACES & CONNECTORS

Analog input connector	VGA
Digital input connector	DVI-D
HDCP	yes
	VGA, DVI-D

### SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, NL, PL, RU, JP, Chinese - traditional and simplified) and 5 front controls (Power, Select/ Input, Scroll up/ Audio, Scroll down/ i-Style Colour, Menu)
User controls	auto adjust, luminance (contrast, brightness, ACR, ECO), input select, audio (volume, mute), colour adjust, information, manual image adjust (H./V. position, clock, phase, sharpness), setup menu (language select, OSD position, OSD time out, OSD background, opening logo, LED), recall
Speakers	2 x 1 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Safety	CE, TÜV-Bauart, VCCI-B, TCO, GOST-R
Height adjustment	130 mm
Rotation (pivot function)	90°
Swivel Stand	90°; 45° left; 45° right
Tilt angle	22° up; 3° down
VESA mounting	100 x 100 mm
Colour	White

### ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista/ 7 / 8
Included accessories	power cable, VGA cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide