



ProLite E2773HS

The ProLite E2773HS LED-backlit 27" monitor features a stunning 1 ms response time and a FHD (1920x1080) resolution. The high brightness and contrast offer the user clear and vivid images, and the HDMI, DVI and VGA connections ensure compatibility across a range of devices including games consoles and workstations. The X-Res Technology feature helps to deliver best quality pictures even if the source is not perfect, like movies made with mobile device.

DISPLAY CHARACTERISTICS

| | |
|--------------------|---|
| Diagonal | 27" |
| Panel | TN |
| Display area h x w | 336.3 x 597.9 mm; 13.2" x 23.5" |
| Response time | 1 ms |
| Contrast | 1 200 : 1 typical |
| Contrast | 5 000 000 : 1 ACR |
| Brightness | 300 cd/m ² typical |
| Viewing zone | horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.311 x 0.311 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 24 - 82 KHz |
| Vertical sync | 55 - 76 Hz |
| Synchronization | Separate Sync |
| Aspect ratio | 16 : 9 |

POWER MANAGEMENT

| | |
|-------------------|---|
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | 29 W typical; max. 0.5 W in Power management mode |
| Power management | VESA DPMS, ENERGY STAR® |

DIMENSIONS & WEIGHT

| | |
|----------------------|----------------------|
| Dimensions w x h x d | 647 x 454.5 x 239 mm |
| Weight | 5.3 kg |

INTERFACES & CONNECTORS

| | |
|-------------------------|--------------------|
| Analog input connector | VGA (D-Sub) |
| Digital input connector | DVI-D, HDMI |
| HDCP | yes |
| Output connector | headphone socket |
| | D-Sub, DVI-D, HDMI |

SPECIAL FEATURES

| | |
|-------------------|--|
| Apple - Mac | All iiyama monitors are compatible with Apple-Macintosh computers. |
| Plug & Play | VESA DDC2B™ |
| Controls | Via OSD in 8 languages (EN, DE, FR, NL, PL, Chinese, JP, RU) and 5 front controls (Power, Select/ Input select, Scroll up/ X-Res Technology, Scroll down/ i-Style Colour, Menu) |
| User controls | auto adjust, picture adjust (contrast, brightness, ACR, ECO, OD, X-Res Technology), input select, audio adjust (volume, mute, HDMI audio), colour adjust (information, manual image adjust (clock, H/V position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, opening logo, LED), memory recall |
| Speakers | 2 x 2 W (Stereo) |
| Anti-theft-device | Kensington-lock™ prepared |
| Safety | TÜV-Bauart, PSE, CE, VCCI-B, CU |
| Tilt angle | 20° up; ° down |
| VESA mounting | 100 x 100 mm |
| Colour | Black |

ACCESSORIES

| | |
|----------------------|--|
| Driver | Windows 95 / 98 / 2000 / ME / XP / Vista/ 7 / 8 |
| Included accessories | power cable, VGA (D-Sub) cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide |