



PROJECTOR

**X100-4K**


## Key Features

- True 4K UHD visual experience
- Cinema SuperColor+™ Technology with 125% Rec.709
- 2nd generation LED technology with 30,000 hours lifespan
- Wide H/V lens shift for flexible installation
- Extremely low fan noise (20 dB) ensuring pure viewing



## Product Description

ViewSonic's X100-4K is a 2,900 LED Lumens 4K UHD home cinema projector of superior performance and great value. Fulfilling movie lovers' dreams with 2nd generation LED technology, for cinematic colours and reliable light source life, low fan noise (20 dB), wide H/V lens shift and optical zoom combined into a proprietary design, the X100-4K serves as a professional choice for every home.



1. IR Receiver(Front & Top)
2. Lens
3. Motorised Lens Cover
4. Lens Shift Control Knob
5. Zoom Ring
6. HDMI 2.0/HDCP 2.2
7. LAN

8. S/PDIF Out
9. Service
10. Wire IR
11. Control
12. USB Reader 3.0(5V/2A)
13. RS232
14. 12V Trigger X2

15. Audio Out
16. Keypad
17. Wi-Fi Dongle(Optional)
18. AUX
19. Computer In

**Visit Us**

[www.viewsonic.com](http://www.viewsonic.com)



**SPECIFICATION**

Native Resolution:	3840x2160
Brightness:	2900 (LED Lumens)
Contrast Ratio:	3000000:1
Display Colour:	1.07 Billion Colours
Light Source Type:	LED
Light Source Life (hours) with Normal Mode:	up to 30000
Lamp Watt:	RGBB LED
Lens:	F1.8-1.825, f=12.62-15.13mm
Projection Offset:	0%
Throw Ratio:	1.2-1.44
Optical Zoom:	1.2x
Image Size:	40"-200"
Throw Distance:	1.06m-6.37m , (100
Keystone:	+/- 40° (V)
Lens Shift V. Range:	+65%, -0%
Lens Shift H. Range:	+25%, -25%
Audible Noise (Normal):	23dB
Audible Noise (Eco):	20dB
Local Storage:	Total 16GB , (12GB available storage)
Input Lag:	66.8 ms
Resolution Support:	VGA(640 x 480) to , 4K(3840 x 2160)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P
Horizontal Frequency:	15K-135KHz
Vertical Scan Rate:	23-120Hz

**INPUT**

Computer in (share with component):	1
HDMI:	4, (HDMI 2.0, HDCP 1.4/2.2)
Audio-in (3.5mm):	1
USB Type A:	2, (USB3.0 Reader x1,, USB2.0 Reader x1)
RJ45 Input (Internet):	1
Wifi Input:	1( 5Gn)

**OUTPUT**

Audio out (3.5mm):	1
S/PDIF:	1
Speaker:	20W Cube x2
USB Type A (Power):	2, (USB3.0 - 5V/2A x1,, USB2.0 - 5V/900mA x1,, share with USB A Input)
12V Trigger (3.5mm):	2

**CONTROL**

RS232 (DB 9-pin male):	1 (Female)
RJ45 (LAN control):	1
USB Micro B-2.0 (Services):	1

**OTHERS**

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz, (AC in)
Power Consumption:	Normal: 200W, Standby: <0.5W
Operating Temperature:	0~40°C
Net Weight:	7.60kg
Dimensions (WxDxH) with Adjustment Foot:	416x463x183mm

OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages
---------------	---

**STANDARD ACCESSORY**

Power Cord:	1 (1.8m)
Remote Control:	1, (w/ backlit )
QSG:	Yes



Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

