

DISPLAY

Screen Size	55"
Panel Technology	IPS
Back Light Type	Direct
Aspect Ratio	16:9
Native Resolution	1920 x 1080
Refresh Rate	60Hz
Brightness (Typ.)	700 nits
Contrast Ratio	1100:1
Dynamic Contrast Ratio	500,000:1
Color gamut	NTSC 72%
Viewing Angle (H x V)	178° x 178°
Color Depth	10bit, 1.07 Billion colors
Response Time (G to G)	8ms
Surface Treatment (Haze)	28%
Lifetime (Typ.)	60,000 Hrs
Operation Hours (Hours/Day)	24/7
Portrait / Landscape	Yes / Yes

SOUND

Speaker	No
---------	----

CONNECTIVITY

HDMI	Yes (x2), HDCP2.2
------	-------------------

DP	Yes, HDCP2.2
----	--------------

DVI-D	Yes, HDCP1.4
-------	--------------

Audio In	Yes
----------	-----

RS232C In	Yes
-----------	-----

RJ45(LAN)	Yes
-----------	-----

IR In	Yes
-------	-----

USB	Yes, USB2.0 Type A
-----	--------------------

DP Out	Yes
--------	-----

Audio Out	Yes
-----------	-----

RS232C OUT	Yes
------------	-----

MECHANICAL

Bezel Color	Black
-------------	-------

Bezel Width	0.44mm Even Bezel
-------------	-------------------

Weight	40.6 lbs / 18.4 kg
--------	--------------------

Packed Weight	52.0 lbs. / 23.6 kg
---------------	---------------------

Monitor Dimension (W x H x D)	47.7 x 26.8 x 3.4 in. 1210.51 x 681.22 x 86.5mm
-------------------------------	---

Shipping Dimensions (W x H x D)	53.3 x 33.7 x 10.4 in. 1353 x 855 x 263 mm
---------------------------------	--

Handle	Yes
--------	-----

IP Rating	IP5X
-----------	------

VESATM Standard Mount Interface	600 x 400
---------------------------------	-----------

FEATURES

Internal Memory	8GB
-----------------	-----

Temperature Sensor	Yes
--------------------	-----

BLU Sensor	Yes
------------	-----

Acceleration(Gyro) Sensor	Yes
---------------------------	-----

Smart Calibration	Yes
-------------------	-----

Local Key Operation	Yes
---------------------	-----

webOS Signage version	webOS 4.1
-----------------------	-----------

Local Contents Scheduling	Yes
---------------------------	-----

Group Manager	Yes
---------------	-----

USB Plug & Play	Yes
-----------------	-----

Fail over	Yes
-----------	-----

No Signal Image	Yes
-----------------	-----

RS-232C Sync	Yes
--------------	-----

Local Network Sync	Yes
--------------------	-----

Video Tag	Yes (x4)
-----------	----------

Play via URL	Yes
--------------	-----

Screen Rotation	Yes
-----------------	-----

External Input Rotation	Yes
-------------------------	-----

Gapless Playback	Yes
------------------	-----

Tile Mode Setting	Yes (Max. 15X15)
-------------------	------------------

Setting Data Cloning	Yes
----------------------	-----

FEATURES

SNMP	Yes
------	-----

FEATURES

ISM Method	Yes
------------	-----

Auto Set ID	Yes
-------------	-----

Status Mailing	Yes
----------------	-----

Control Manager	Yes
-----------------	-----

Crestron Inside	Yes
-----------------	-----

Smart Energy Saving	Yes
---------------------	-----

PM mode	Yes
---------	-----

Wake on LAN	Yes
-------------	-----

Network Ready	Yes
---------------	-----

HDMI-CEC	Yes
----------	-----

SI Server Setting	Yes
-------------------	-----

webRTC	Yes
--------	-----

Pro:Idiom	Yes
-----------	-----

W/B Setting by Grey scale	Yes
---------------------------	-----

Scan Inversion	Yes
----------------	-----

ELECTRICAL

Power Supply	100-240 Vac, 50/60 Hz
--------------	-----------------------

Power Type	Built-In Power
------------	----------------

Typical Power Consumption	210 W
---------------------------	-------

Max Power Consumption	250 W
-----------------------	-------

Typical Heat Dissipation	717 BTU/Hr
--------------------------	------------

Max Heat Dissipation	853 BTU/Hr
----------------------	------------

Smart Energy Saving	110 W
---------------------	-------

DPM	0.5 W
-----	-------

Power off	0.5 W
-----------	-------

OPS compatible	Yes (Piggyback)
----------------	-----------------

OPS Power built in	No
--------------------	----

Operation Temperature	32°F to 104°F 0°C to 40°C
-----------------------	---------------------------

Operation Humidity	10% to 80%
--------------------	------------

LG SOFTWARE & SERVICES*

SuperSign CMS	Yes
---------------	-----

LG SOFTWARE & SERVICES*

SuperSign Contro	Yes
------------------	-----

SuperSign Control+	Yes (optional for purchase)
--------------------	-----------------------------

SuperSign White Balance	Yes (optional for purchase)
--------------------------------	-----------------------------

SuperSign Media Editor	Yes (optional for purchase)
-------------------------------	-----------------------------

LG ConnectedCare	Yes (optional for purchase)
-------------------------	-----------------------------

WARRANTY & OTHER

Warranty	3 Year Limited
-----------------	----------------

Regulatory	FCC Class "B" / CE / KC
-------------------	-------------------------

Environmental	ErP / Energy Star 8.0
----------------------	-----------------------

Onscreen Display Languages	English, French, German, Spanish, Italian, Korean, Chinese (Original & Simplified), Portuguese (Portugal & Brazil), Swedish, Finnish, Norwegian, Danish, Japanese, Russian, Dutch, Czech, Greek, Turkish, Arabic
-----------------------------------	--

Included Accessories	Remote Control (includes 2 batteries), Power Cord, RS232C cable, LAN cable, DP cable, IR Receiver, Guide Bracket, Screws, Manual
-----------------------------	--

Optional Accessories	OPS Kit (KT-OPSF)
-----------------------------	-------------------
