

All Spec

PANEL

Screen Size

49"

Aspect Ratio

16 : 9

Brightness (Typ., cd/m²)

700

Dynamic CR

500,000 : 1 (The luminosity ratio of Full Black/Full White color on video input condition.)

Response Time

8 ms (G to G)

Life Time (Typ.)

60,000 Hrs

Orientation

Landscape & Portrait

Panel Technology

IPS

Native Resolution

1,920 x 1,080 (FHD)

Contrast Ratio

1,300:1

Viewing Angle (H x V)

178 x 178

Surface Treatment

3%

Operation Hours

24 Hrs

CONNECTIVITY

Input

HDMI, DP, DVI-D, RGB, Audio, USB

Output

DP, Audio

External Control

RS232C In/out, RJ45(LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color

Black

Bezel Width

2.25 mm (T/L), 1.25 mm (B/R)

Monitor Dimension (W x H x D)

1,077.6 x 607.8 x 89.7 mm

Weight (Head)

17.8 kg

Carton Dimensions (W x H x D)

1,214 x 778 x 263 mm

Packed Weight

22.8 kg

Handle

Yes

VESA™ Standard Mount Interface

600 x 400 mm

ENVIRONMENT CONDITIONS

Operation Temperature
0°C to 40°C

Operation Humidity
10 % to 80 %

POWER

Power Supply
100-240V~, 50/60Hz

Power Type
Built-In Power

POWER CONSUMPTION

Typ./Max
140 W / 165 W

Smart Energy Saving
75 W

CERTIFICATION

Safety
CB / NRTL

EMC
FCC Class "A" / CE / KC

ErP / Energy Star
Yes(EU Only) / Yes (Energy Star 8.0)

MEDIA PLAYER COMPATIBILITY

OPS type compatible
No

SOFTWARE COMPATIBILITY

Content Management Software
SuperSign CMS

Control and Monitoring Software
SuperSign Control/Control+

ACCESSORY

Basic
Remote Controller, Power Cord, RS232C
Cable, DP Cable, IR Receiver, Guide Bracket,
Screws, Manual

Optional
Wall Mount (Landscape: WM-L640V,
Portrait: WM-P640V)

COMPLIANCE INFORMATION



[Dismantling information\(49VL7F-A\)](#)



[EU Energy label 2019\(49VL7F-A\)](#)



[EU Energy label 2019\(49VL7F-AK\)](#)



[UK Energy label 2019\(49VL7F-A\)](#)



[UK Energy label 2019\(49VL7F-AK\)](#)



[Product information sheet \(49VL7F-A\)](#)



[Product information sheet \(49VL7F-AK\)](#)



[WEB INFO\(49VL7F-A\)](#)



MORE COMPLIANCE INFORMATION >