

newline

all office

all office ltd

FutureVisuals

NEW 2025




NEXT-GEN DYNAMIC COMMUNICATION

The **Newline STV+** enhances business presentations, classroom lessons, and digital signage with stunning **4K visuals**, up to **XDR 2000 nits** brightness, and an ultra-high **7000:1 contrast ratio**, all wrapped in a sleek, modern design. Available in a wide range of sizes from **43"** to **115"**, it fits perfectly into any environment. **Cast+** enables instant content sharing from any device, while seamless integration with **Signage Pro** software streamlines **content management**. **Display Management Plus** centralizes control of settings and updates across all screens.



GO BEYOND WITH CLICK2CAST! Compatible with the Newline Click2Cast dongle, a hassle-free hardware solution for one click casting. Just a single button to initiate wireless screen casting effortlessly.



NEWLINE INTERACTIVE ECOSYSTEM The Newline Interactive Ecosystem streamlines operations with seamless tools for content sharing, signage management, and display control, optimizing workflows

 Edge-to-Edge Ultra Slim Design	 Crystal Clear Image	 4K HD Resolution
 Day Long Run	 High Quality Sound System	 Wide Range of Sizes

CAST+ **CAST** **BROADCAST** **DISPLAY MANAGEMENT PLUS**
APP STORE **SIGNAGE PRO**

43" 55" 65" 75"
85" 98" 115"

PRODUCT SPECIFICATIONS

v06.25

MODEL	STV+ 43"	STV+ 55"	STV+ 65"	STV+ 75"	STV+ 85"	STV+ 98"	STV+ 115"
SKU	STV-4324-Plus	STV-5524-Plus	STV-6524-Plus	STV-7524-Plus	STV-8524-Plus	STV-9824-Plus	STV-11524-Plus

PANEL							
Display Type	Direct LED	Direct LED	Direct LED	Direct LED	Direct LED	Direct LED	QD-Mini LED
Display Area	941 x 529 mm	1210 x 680 mm	1428 x 804 mm	1650 x 928 mm	1872 x 1053 mm	2159 x 1214 mm	2534 x 1425 mm
Display Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD	3840 x 2160 4K UHD
Colours	1,07 Billion	1,07 Billion	1,07 Billion	1,07 Billion	1,07 Billion	1,07 Billion	1,07 Billion
Brightness	300 cd/m ²	300 cd/m ²	300 cd/m ²	400 cd/m ²	400 cd/m ²	600 cd/m ²	XDR 2000 cd/m ²
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1	7000:1
Response Time	6,5 ms	6,5 ms	6,5 ms	6,5 ms	6,5 ms	6,5 ms	6,5 ms
Viewing Angle	178°	178°	178°	178°	178°	178°	178°
Operating Time	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days	24 hrs / 7 days
Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Display Lifetime	50 000 hours	50 000 hours	50 000 hours	50 000 hours	50 000 hours	50 000 hours	50 000 hours
Haze	2%	2%	2%	2%	2%	25%	2%

POWER CONSUMPTION							
Standard Mode	58 W	84 W	94 W	111 W	138 W	140 W	161 W
Standby Mode	0,5 W	0,5 W	0,5 W	0,5 W	0,5 W	0,5 W	0,5 W

SPEAKERS							
Speakers Position	Back	Back	Back	Back	Back	Back	Back
Speakers Max. Power	2 x 15 W	2 x 15 W	2 x 15 W	2 x 15 W	2 x 15 W	2 x 15 W	8 x 10 W
Subwoofer	x	x	x	x	x	x	2 x 20 W
Sound System	2.0	2.0	2.0	2.0	2.0	2.0	6.2.2

SMART SYSTEM	
CPU GPU RAM	4 x A73 2,20 GHz, 4 x A53 2,20 GHz
Storage	Arm Mail-G52
Operating System	4 GB
Wi-Fi Bluetooth	16 GB
	Android 14
	5
	5.0

PORTS I/O	
Rear	1 x USB Type A 3.0, 1 x USB Type A 2.0, 3 x HDMI in 2.1 with HDCP 2.2 (4K@30 Hz), 1 x Audio Line Out, 1 x SPDIF Out, 1 x LAN In (RJ45), 1 x RS232, 1 x AV In

DIMENSIONS / WEIGHT / STORAGE								
Net Weight (Kg)	6,5	10,5	16,5	23,1	28,8	59	94,3	
Gross Weight (Kg)	9	14,3	23,1	33,2	41,1	86,5	131,5	
Outline Dim. (mm)	957 x 559 x 86	1226 x 709 x 87	1446 x 831 x 85	1668 x 956 x 88	1890 x 1081 x 91	2182 x 1247 x 111	2564,6 x 1468,6 x 61,7	
Packaging Dim. (mm)	1075 x 142 x 652	1350 x 144 x 837	1600 x 164 x 960	1840 x 190 x 1103	2030 x 192 x 1250	2390 x 280 x 1500	2780 x 1680 x 280	
Operating/ Storage Temperature	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	0°C - 40°C / -20°C - 60°C	
Operating/ Storage Humidity	10% - 90% / 20% - 80% (non-condensing)	10% - 90% / 20% - 80% (non-condensing)	10% - 90% / 20% - 80% (non-condensing)	10% - 90% / 20% - 80% (non-condensing)	10% - 90% / 20% - 80% (non-condensing)	10% - 90% / 20% - 80% (non-condensing)	10% - 90% / 20% - 80% (non-condensing)	
VESA (mm)	300 x 300	400 x 300	400 x 300	400 x 300	500 x 400	800 x 400	1000 x 500	

EXTRA FEATURES	
Wake-on-LAN	✓
Wake-on-WiFi	✓
Firmware Update	Via OTA
HDMI EDID	1.4 and 2.0
HDMI Arc	HDMI 2.1 Support HDMI ARC/eARC
Hotspot	2.4 GHz and 5.0 GHz
Failover	✓

NEWLINE COMPATIBILITY	
Software Ecosystem	Cast, Broadcast, App Store, Display Management Plus, Signage Pro, Cast+ (Available in App Store)
Accessories	Click2Cast