

DATA SHEET

CAMBRIDGE Qt X 805/805D

SOUND MASKING CONTROL MODULE



The Cambridge Qt™ X 805/805D control module is a sound masking generator, controller, third octave band equalizer and amplifier, with two auxiliary audio inputs allowing for distribution of audio from paging controllers and/or (background) music players. The Qt X 805/805D controls sound masking speakers/emitters in both direct-field and indirect (in-plenum) installations—or a mix of both. Each of the eight amplified output speakers/emitters can be independently adjusted for masking and aux audio levels and spectra. When multiple Qt X controllers are included in a single system, audio inputs can be shared across all controllers via AVB or Dante (805/D).

FEATURES

- Compatible with DynasoundPro™ loudspeakers and emitters
- Supports up to eight zones of amplified speakers matched with eight zones of pre-amp outputs
- AVB or Dante (805/D) media network
- Two audio inputs for paging and music
- Contact closure integrates with fire alarm systems
- Front panel with LCD
- Panel lock via software control
- Auto ramping
- Event scheduling
- Adjustable equalizer for masking and audio inputs
- Eight included non-correlated sound masking audio sources (one for each output)
- Built-in clock with system NTP support
- Rack mount bracket included, optional wall mount bracket also available
- Dual network ports (media / control)
- Third-party control API/Ethernet
- CE marked, UL listed, and RoHS compliant
- Met Works with WELL licensing criteria for sound masking
- Covered by Biamp Systems' five-year warranty
- Manufactured in the U.S.A.
- TAA compliant
- GSA eligible

ARCHITECTS & ENGINEERS SPECIFICATION

The network sound masking processor shall be a Qt X 805/805 D. The unit shall be AVB or Dante capable. The unit shall be capable of providing eight independent amplifier channels, designed to power and independently control up to eight DynasoundPro sound masking speakers with simultaneous support for eight matched zones of pre-amplifier outputs for use with an auxiliary amplifier for 70V masking applications. The unit shall be capable of time-of-day masking level control; per-zone settings shall be available for day/night levels and start times, ramping interval, and weekday/Sat/Sun behavior. Each controller shall include eight non-correlated sound masking generators to minimize comb filtering between speakers or speaker runs. Units that do not support individual speaker control or are designed to control speakers in groups of two or more ganged speakers are not acceptable. Units requiring proprietary network switches and hardware are not acceptable. The unit shall meet all requirements of Underwriters Laboratories, the US and Canadian National Electrical Codes, FCC Part 15, and all pertinent UK and EU codes. The controller shall be CE marked, UL listed, and shall be compliant with the RoHS directive. Warranty shall be five years. The controller shall be Qt X 805/805D.

Qt X 805/805D SPECIFICATIONS

Output Equalization		Power Supply	
Sound Masking (100Hz - 10kHz):	ISO 1/3 Octave Bands	Operating Voltage:	100-240VAC 50/60Hz
Music/Paging (125Hz - 8kHz):	ISO 1/3 Octave Bands	Current Draw:	0.5A
Number of Non-Correlated Masking Sources	8	Output:	48VDC @1.04A (50W Max)
Masking Level Adjustment:	0.5dB steps	Max. Power Consumption (48VDC):	24W
Audio Inputs		Overall Dimensions	
Input Connector Type:	Captive Screw Terminal	Height:	3.5 inches (89mm)
Number of Inputs:	2 (Stereo or Mono)	Width:	14 5/8 inches (371.5mm)
Input Level:	+24dBu (12.3VRMS max)	Depth:	3.8 inches (97mm)
Input Gain Range:	6dB steps	Weight:	3.8lbs(1.75kg)(with rack mount bracket installed)
Input Level Adjustment:	1dB steps	Environmental:	
Input Impedance:	8kΩ	Ambient Operating Temperature Range:	
Remote Control		40 - 90° F (4 - 32° C)	
Connector Type:	Captive Screw Terminal	Humidity:	
Input Type:	Contact Closure (Normally Open)	0-95% relative humidity (non-condensing)	
Number of Inputs:	2	Altitude:	
Output Type:	Logic Status (5VDC)	0-6,600 ft (0-2000m) MSL	
Number of Outputs:	2	Compliance:	
		FCC Part 15B (USA)	
		UL Listed (USA and Canada)	
		CE Marked (Europe)	
		RoHS Directive (Europe)	
Amplified Audio Outputs			
Output Connector Type:	Captive Screw Terminal		
Number of Amplified Outputs:	8		
Nominal Output Impedance:	4Ω		
Pre-Amplifier Audio Outputs			
Number of Outputs:	8		
Nominal Output Impedance:	207Ω		

¹ Specifications based on use of Qt Emitters / Qt Active Emitter array and based on published layout practices

Qt X 805/805D BACK PANEL



Biamp, Qt, and Qt X are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.