

75" BenQ Board Pro – All in One Interactive Display Series Spec Sheet		BenQ/FutureVisuals		
All Specifications				
Panel				
	Specification	Value		
	Screen size	75"		
	Panel type	IPS		
	Active area	1650.2 × 928.2 mm		
	Aspect ratio	16:9		
	Resolution	UHD 3840 × 2160 pixels		
	Response time	8 ms		
	Color depth	10-bit		
	Orientation	Landscape		
	Operation hours	18 hours / 7 days		
	Panel brightness (typical)	450 nits		
	Contrast ratio (typical)	1500:1		
	Dynamic contrast ratio	50,000:1		
	Color gamut	90% NTSC		
	Light life (typical)	50,000 hrs		
Glass				
	Specification	Value		
	Germ-resistant coating	Nano-ionic silver		
	Anti-glare coating	Yes		
	Hardness	9H tempered		
Touch Screen				
	Specification	Value		
	Touch technology	Capacitive touch		
	Touch points	up to 50		
	Response time	< 5 ms		
System				
	Specification	Value		
	GPU	Arm Mali-G57 MC2		
	CPU	Arm Cortex-A78 × 2 + Cortex-A55 × 6		
	NPU	10 TOPS		

Memory / Storage	16GB / 256GB			
OS	Android 15.0 (EDLA)			
Connectivity				
Specification	Value			
HDMI (in / out)	1 × HDMI 2.0 / No			
USB-A	2 × USB 3.0			
USB-C	1 × USB 2.0 + 1 × USB 3.0 (PD 100 W)			
USB-C out	1 × Type-C (2.0 data / video out / audio out / touch)			
3.5 mm Line out	Earphone × 1			
Slot-in PC (OPS)	1			
Wi-Fi	Wi-Fi 6			
Bluetooth®	Bluetooth 5.4			
Ethernet LAN	10 / 100 / 1000 Mbps (Android), 10 / 100 / 1000 Mbps (OPS) × 2			
RS-232	1 / 0			
Built-in Peripherals				
Specification	Value			
NFC sensor	Yes			
Ambient light sensor	Yes			
IR sensor	Yes			
Microphone	8-microphone array (range: up to 12 m / 39 ft)			
Speaker	2 × 25 W			
Camera	1 (50MP, FOV 160°)			
Subwoofer	1 × 40 W			
Power				
Specification	Value			
ENERGY STAR®	Yes			
Power	AC 100–240V 50/60Hz			
Standby power consumption	< 0.5 W			
Typical power consumption	95 W			
Physical				
Specification	Value			
Dimensions (W × H × D)	1720.6 × 1022 × 98.5 mm (67.7 × 40.2 × 3.9 inch)			
Shipping dimensions (W × H × D)	1880 × 1135 × 220 mm (74 × 44.7 × 8.7 inch)			

Weight (product / shipping)	45.1 kg / 58.2 kg (99.4 lbs / 128.3 lbs)				
Mount (screws)	VESA 800 × 400 mm (4 × M8 × 25L)				
Environment					
Specification	Value				
Operating temperature	0°C ~ 40°C (32°F ~ 104°F)				
Storage temperature	-10°C ~ 60°C (14°F ~ 140°F)				
Storage humidity	20% ~ 90% RH (non-condensing)				
Operating humidity	20% ~ 80% RH (non-condensing)				
Software					
Specification	Value				
Whiteboarding	EZWrite 6.0				
Wireless screen sharing	InstaShare 2				
Device management	DMS				
Account management	AMS				
Flicker Free	Yes				
Quick access tool	Floating Tool				
Broadcast system	X-Sign Broadcast				
Low Blue Light	Yes				
Accessories					
Specification	Value				
Cables	1 × HDMI (3 m / 9.8 ft), 1 × USB-C (1.5 m / 4.9 ft), 1 × USB-C to A (3 m / 9.8 ft), 1 × RS232 (1.8 m / 5.9 ft)				
Wall Mount (with shipment)	1				
Stylus	Active × 1, Passive × 1				