

MAXHUB CMA Digital Signage Display Series Specifications							FutureVisuals/MAXHUB
Spec	ND43CMA	ND55CMA	ND65CMA	ND75CMA	ND86CMA	ND98CMA	
Screen Size	43"	55"	65"	75"	86"	98"	
Screen Type	VA	VA	ADS	ADS	ADS	ADS	
Brightness	500 nits	500 nits	500 nits	500 nits	500 nits	500 nits	
Contrast Ratio	5,000:1 (Typ) / 1,000,000:1 (Dynamic)	1,000,000:1 (Dynamic) / 5,000:1 (Typ)	5,000:1 (Typ) / 1,000,000:1 (Dynamic)	1,000,000:1 (Dynamic) / 5,000:1 (Typ)	1,200:1 (Typ) / 1,000,000:1 (Dynamic)	1,000,000:1 (Dynamic) / 1,200:1 (Typ)	
Resolution	4K UHD	4K UHD	4K UHD	4K UHD	4K UHD	4K UHD	
Viewing Angle	178° (H/V)	178° (H/V)	178° (H/V)	178° (H/V)	178° (H/V)	178° (H/V)	
OPS Capable	No	No	80pin / OPS62A	80pin / OPS62A	80pin / OPS62A	80pin / OPS62A	
Wifi Module	SI07B	SI07B	SI07B	SI07B	SI07B	SI07B	
Speakers	2x16W	2x16W	2x16W	2x16W	2x16W	2x10W	
Thickness of Bezel	9.9mm	9.9mm	15.9mm	15.9mm	15.9mm	26mm	
Portrait/Landscape Mode	Yes	Yes	Yes	Yes	Yes	Yes	
Wall Mounting Mode	WIB4722A	WIB4722A	WIB9080A	WIB9080A	WIB9080A	WIB9080A	
Operation Hours	24/7	24/7	24/7	24/7	24/7	24/7	
Life Time	≥50000 hours	≥50000 hours	≥50000 hours	≥50000 hours	≥50000 hours	≥50000 hours	
N.W (kg/lb)	9.90 kg / 21.83 lb	13.40 kg / 29.54 lb	25.40 kg / 56.0 lb	34.65 kg / 76.40 lb	43.15 kg / 95.13 lb	69.90 kg / 154.10 lb	