DATA SHEET
APPRIMO TOUCH 10 UCX-T
TABLETOP TOUCH PANEL CONTROL



Control your video meetings with ease using a 10” floating tabletop touchscreen display designed for sharp, easy-to-read visuals from anywhere at the table.

FEATURES

- One cable does it all — A single cat-cable connection provides both data and power via PoE+ from Devio UCX. Plug it in and it auto pairs to Devio UCX.
- Instant, glare-free response — An instant-response capacitivetouch layerwith an optically bonded LCD reduces glare and keeps every tap responsive.
- Stays looking pristine — An anti-fingerprint coating keepsthedisplayclean through daily use.
- Modern, rigid profile — Unique stamped metal constructiondelivers a thin, rigid build that looks as good as it feels.
- Stays put on the table — An anti-slip foot keeps the panelsecurelyinplace, no matter how often it’s used.
- Wakes as you walk in — A proximity sensor wakes the devicethemomentyou enter the room.
- BYOM out of the box — A USB-C port enables BYOM andcontentsharing right at the table.
- Cable clutter, solved — Built-in cable management keepsthetabletopclean and professional.

The Apprimo Touch 10 UCX-T is a premium 10-inch tabletop touch panel designed for Devio UCX meeting room systems, making video meeting control simple, responsive, and visually clear. Its floating display, optically bonded LCD, anti-glare and anti-fingerprint surface, and instant-response capacitive touch layer create a refined experience worthy of being a room centerpiece.

The thin, stamped-metal construction provides a rigid, modern profile, while the anti-slip foot keeps the controller securely in place on the table. A proximity sensor wakes the panel as users enter the room, and a single-cable PoE+ connection from Devio UCX simplifies both installation and power.

Built-in USB-C enables convenient BYOM and content sharing at the table, with optional power adapter support for laptop charging and integrated cable management for a clean, professional installation.

ARCHITECTS & ENGINEERS SPECIFICATIONS

The touch panel shallbe a dedicated touch controller for unified communications room systems. The touch panel shall utilize the Microsoft Device Ecosystem Platform (MDEP) operating system based on Android 15. The touch panel shall provide native support for Microsoft Teams Rooms for Android Appliance. The touch panel shall be compatible with the Biamp Devio™ UCX 1000, UCX 2000, and UCX 3000 UC compute devices. The touch panel shall provide a 10.1-inch diagonal IPS LCD display with 1920 x 1200 resolution and auto-adjusting brightness up to 380 cd/m^2. The touch panel shall provide a capacitive touchscreen optically bonded to the LCD, with an anti-fingerprint coating and diffuse-texture finish. The touch panel shall include an ambient light sensor for automatic brightness adjustment, an ultrasonic beacon for Microsoft Teams Rooms proximity join, and a motion sensor to wake the system on motion. The touch panel shall provide one USB-C input supporting DisplayPort 1.4a Alt Mode for content sharing and BYOM (Bring Your Own Meeting) switching at up to 4K at 30 Hz. The touch panel shall provide one Ethernet port (100/1000) for primary LAN connection and shall be powered as a PoE+ Class 4 powered device, with an optional 100W USB-C power supply available for Wi-Fi deployments and 65W USB-C device charging. The touch panel shall provide Wi-Fi 6 wireless LAN. The touch panel shall support remote status monitoring via Biamp Workplace; Microsoft 365 Admin, Entra ID, and Intune management via MDEP; and Teams Admin Center and Teams Rooms Pro Management Portal for Microsoft Teams Rooms. The touch panel shall provide platform security including Secure Boot and Signed Firmware Update, hardware-based attestation with Microsoft PKI and Microsoft Secure Pairing, and network security including 802.1X, Wi-Fi WPA3, and proxy server support. The touch panel shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be three years. The touch panel shall be the Biamp Apprimo™ Touch 10 UCX-T.

APPRIMO TOUCH 10 UCX-T SPECIFICATIONS

Platform:

Operating System:	Microsoft Device Ecocsystem Platform (MDEP) based on Android 15
UC Vendors:	Microsoft Teams Rooms for Android
Compatiblity:	Devio UCX 1000, Devio UCX 2000, Devio UCX 3000
Processor:	Qualcomm Dragonwing QCS5430
Memory:	8 GB

Display:

Size:	10.1” diagonal IPS LCD
Resolution:	1920 x 1200
Brightness:	380 cd/m^2, auto-adjusting
Touch Screen:	Capacitive touch, optically bonded with LCD, anti-fingerprint coating, diffuse texture

Sensors:

Ambient Light:	Auto-brightness
Ultrasound:	Ultrasonic beacon for Microsoft Teams Rooms proximity join
Motion Detection:	Wake system on motion

Ports:

USB-C Input:	Content Sharing and BYOM Switch, USB-C DP 1.4a Alt Mode, 4K 30Hz
USB-C Charging:	65W USB-C device charing when optional power supply is connected
Power Input:	Optional 100W USB-C power supply for Wi-Fi connections and 65W device charging

Network and Wireless:

Ethernet:	Primary LAN, 100/1000, PoE+ Class 4 PD
Wireless:	Wi-Fi 6, 802.11ac

Manageability:

Biamp Workplace:	Remote status monitoring, Biamp Launch Report Cards
MDEP:	Microsoft 365 Admin, Entra ID, Intune
Microsoft Teams Rooms:	Teams Admin Center, Teams Rooms Pro Management Portal

Security:

Platform:	Secure Boot, Signed Firmware Update
MDEP:	Hardware-based attestation with Microsoft PKI, Microsoft Secure Pairing
Network:	802.1X, Wi-Fi WPA 3, Proxy Server

Overall Dimensions:

Height:	2.61 inches (66.3 mm)
Width:	9.59 inches (243.6 mm)
Depth:	6.09 inches (154.8 mm)
Weight:	TBD lbs (TBDkg)
Angle:	20°
Anti-Slip Base:	Yes

Power:

PoE Input:	PoE+ Class 4 powered device, 25.5W
External Adapter:	Optional USB-C 100W power supply for Wi-Fi or 65W USB-C device charging
Power Consumption:	< 25.5W, < 100W when charing external USB-C device

Environmental:

Ambient Temperature Range:	32-104° F (0–40° C)
Humidity:	0–98%, non-condensing
Altitude:	0-6,600 feet (0–2000 Meters) MSL

Compliance:

Certifications:	FCC Part 15B (USA)
	Canada ICES-003 (A) / NMB-003 (A)
	CE marked (Europe)
	UL und C-UL listed (USA and Canada)
	RCM (Australia)
	RoHS Directive (Europe)
	Radio Equipment Directive (Europe)

Warranty:

Standard Warranty:	3 years

Accessories:

Optional Accessories:	Apprimo Touch 10 UCX-TMA table mount accessory, Apprimo Touch 10 UCX-PSA power supply accessory

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

Biamp and Apprimo are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.

FutureVisuals